



SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name POWER PLUS
Synonyms HEAVY DUTY TOILET AND URINAL TREATMENT

1.2 Uses and uses advised against

Uses CLEANING AGENT • TOILET CLEANER • URINAL CLEANER

1.3 Details of the supplier of the product

Supplier name ENVIRONMENTAL TECHNOLOGIES GROUP PTY LTD
Address 16 Mallett Rd, Tullamarine, VIC, 3043, AUSTRALIA
Telephone + 61 3 8336 8500
Email info@ecogreen.com.au
Website <http://www.ecogreen.com.au>

1.4 Emergency telephone numbers

Emergency 1800 000 245

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Physical Hazards

Not classified as a Physical Hazard

Health Hazards

Skin Corrosion/Irritation: Category 1B

Environmental Hazards

Not classified as an Environmental Hazard

2.2 GHS Label elements

Signal word DANGER

Pictograms



Hazard statements

H314 Causes severe skin burns and eye damage.

Prevention statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P264 Wash thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

PRODUCT NAME POWER PLUS

Response statements

P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P321	Specific treatment is advised - see first aid instructions.
P363	Wash contaminated clothing before reuse.

Storage statements

P405 Store locked up.

Disposal statements

P501 Dispose of contents/container in accordance with relevant regulations.

2.3 Other hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
ETHOXYLATED LAURYL ALCOHOL	9002-92-0	500-002-6	10 to 30%
METHANESULPHONIC ACID	75-75-2	200-898-6	10 to 30%
DYE(S)	-	-	<0.1%
WATER	7732-18-5	231-791-2	>60%
D-GLUCOPYRANOSE, OLIGOMERS, C8-10-ALKYL GLYCOSIDES	161074-97-1	500-533-3	<5%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
Ingestion	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
First aid facilities	Eye wash facilities and safety shower should be available.

4.2 Most important symptoms and effects, both acute and delayed

Over exposure may result in skin, eye and respiratory burns owing to the acidic nature of the liquid.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

5.2 Special hazards arising from the substance or mixture

Non flammable. May evolve toxic gases (carbon and sulphur oxides) when heated to decomposition. May evolve flammable hydrogen gas in contact with some metals.

5.3 Advice for firefighters

Treat as per requirements for surrounding fires. Evacuate area and contact emergency services. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

- 2X
- 2 Fine Water Spray.
- X Wear liquid-tight chemical protective clothing and breathing apparatus. Contain spill and run-off.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with sodium carbonate or similar, collect and place in suitable containers for treatment and/or disposal. Clean spill site with sodium carbonate solution.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a secured, cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate ventilation and fire protection systems. Store between 5°C and 65°C.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

No exposure standards have been entered for this product.

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended.

PPE

- Eye / Face** Wear splash-proof goggles.
- Hands** Wear PVC or rubber gloves.
- Body** Wear coveralls. When using large quantities or where heavy contamination is likely, wear a PVC apron and PVC boots.
- Respiratory** Where an inhalation risk exists, wear a Type B (Inorganic gases and vapours) respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	LIGHT RED LIQUID
Odour	CHARACTERISTIC ODOUR
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	100°C (Approximately)
Melting point	0°C (Approximately)
Evaporation rate	NOT AVAILABLE
pH	1 - 2
Vapour density	NOT AVAILABLE
Specific gravity	1 (Approximately)
Solubility (water)	SOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT AVAILABLE
Lower explosion limit	NOT AVAILABLE
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), alkalis (e.g. sodium hydroxide) and some metals.

10.6 Hazardous decomposition products

May evolve carbon and sulphur oxides when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity No known toxicity data is available for this product. Based on available data, the classification criteria are not met.

Information available for the ingredients:

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
ETHOXYLATED LAURYL ALCOHOL	384 mg/kg (guinea pig)	--	--
METHANESULPHONIC ACID	648.7 mg/kg (rat)	1000 - 2000 mg/kg (rabbit)	--

Skin Causes burns. Contact may result in irritation, redness, pain, rash, dermatitis and possible burns.

Eye Causes burns. Contact may result in irritation, lacrimation, pain, redness, corneal burns and possible permanent damage.

Sensitisation Not classified as causing skin or respiratory sensitisation.

Not classified as a mutagen.

PRODUCT NAME POWER PLUS**Mutagenicity****Carcinogenicity** Not classified as a carcinogen.**Reproductive** Not classified as a reproductive toxin.**STOT - single exposure** Over exposure may result in mucous membrane irritation of the nose and throat, with coughing and possible burning sensation.**STOT - repeated exposure** Not classified as causing organ damage from repeated exposure. Adverse effects are generally associated with single exposure.**Aspiration** This product does not present an aspiration hazard.

12. ECOLOGICAL INFORMATION

12.1 ToxicityBased on methanesulphonic acid:
LC50 (Freshwater Fish, *Oncorhynchus mykiss*) = 73 mg/L/96hrs.
EC50 (Water Flea) = 12 mg/L EC50 = 48hrs.**12.2 Persistence and degradability**

Expected to be readily biodegradable. Persistence is unlikely, based on information available.

12.3 Bioaccumulative potential

Bioaccumulation is unlikely.

12.4 Mobility in soil

The product is water soluble, and may spread in water systems. Will likely be mobile in the environment due to its water solubility. Highly mobile in soils.

12.5 Other adverse effects

SOIL: If released to soil, this product will dissolve the carbonate based soil materials due to its acidic nature. WATER: A significant amount will reach the water table where dilution and dispersion serve to reduce the acid concentration. Aquatic life may be threatened if the pH falls below 5.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods**Waste disposal** For small amounts (as determined by risk assessment or similar): Wearing the protective equipment detailed above, neutralise to pH 6-8 by SLOW addition to a saturated sodium bicarbonate solution or similar basic solution. Dilute with excess water and flush to drain. Waste disposal should only be undertaken in a well ventilated area. For larger amounts: Dispose in accordance with local regulations.**Legislation** Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	3265	3265	3265
14.2 Proper Shipping Name	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Contains methanesulphonic acid)	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Contains methanesulphonic acid)	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Contains methanesulphonic acid)
14.3 Transport hazard class	8	8	8
14.4 Packing Group	II	II	II

14.5 Environmental hazards

No information provided.

14.6 Special precautions for user

Hazchem code	2X
EMS	F-A, S-B

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
Classifications	Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.
Inventory listings	AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS, or are exempt.

16. OTHER INFORMATION

Additional information	<p>RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.</p> <p>ACIDS: When mixing acids with water (diluting), caution must be taken as heat will be generated which causes violent spattering. Always add a small volume of acid to a large volume of water, NEVER the reverse.</p> <p>PERSONAL PROTECTIVE EQUIPMENT GUIDELINES: The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.</p> <p>HEALTH EFFECTS FROM EXPOSURE: It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.</p>
-------------------------------	--

PRODUCT NAME POWER PLUS**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m ³	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmtglobal.com

[End of SDS]