

MATERIAL SAFETY DATA SHEET

1	PRODUCT AND COMPANY IDENTIFICATION	
	Product Code:	RTKL3 -Full board FL72&FL97 / Half board FE159 & FE161
	Product Name:	Rentokil glue board for Luminus 3 EFK
	Manufacturer:	
	Company name:	Russell IPM Ltd
	Address	68 Third Avenue , Deeside Industrial Park Deeside, Flintshire, CH5 2LA, UK.
	Telephone number	(+44) 1244 281 333
	Fax Number	(+44) 1244 281 878
	Email:	info@russellipm.com
	Web:	www.russellipm.com
	EMERGENCY TELEPHONE	(+44) 1244 287 010
2	COMPOSITION / INFORMATION ON INGREDIENTS	
	Active Ingredients	UV stable hot melt pressure sensitive adhesive made of synthetic polymers of petrochemical origin, mineral oil and UV filters.
	Attractant tablet	
	trap description	
		Craft board white or black printed with grid and coated with hot melt adhesive and laminated with Silicon paper.
	Product function	Insect containment for the purpose of monitoring the target species
3	HAZARD IDENTIFICATION	
	EMERGENCY OVERVIEW	Flammable at temperature over 100C.
4	FIRST AID MEASURES	
	INHALATION	Unlikely mode of exposure . Remove to fresh air. Seek medical advise if symptoms persist.
	EYE	Flush with plenty of water. Seek medical advise if symptoms persist.
	SKIN	Flush with plenty of water. Seek medical advise if symptoms persist.
	INGESTION	Unlikely mode of exposure. Wash mouth with plenty of water. Induce vomiting if swallowed. Seek medical advise.
5	FIRE FIGHTING MEASURES	
	FLAMMABLE PROPERTIES	Flash point Not available
	EXTINGUISHING MEDIA	Water, Dry powder, CO2 or foam
	FIRE FIGHTING INSTRUCTIONS	No Special procedures required

6 ACCIDENTAL RELEASE MEASURES

Instruction for preventing environmental pollution

The material should be prevented from contaminating soil or from entering sewage and drainage systems

7 HANDLING AND STORAGE

HANDLING

- * Avoid contact with skin and eyes.
- * Wash thoroughly after handling.

STORAGE

- * Store in cool, dry and well ventilated place.
- * Keep away from heat, sparks and open flames.
- * Refrigeration is not required.

8 EXPOSURE CONTROL/PERSONAL PROTECTION

- * Standard personal and industrial hygiene practices.
- * No special protective equipment is required under, normal conditions.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance	White craft board with sticky surface covered by silicon release paper.
Odour	Non
Boiling point	Not applicable
Vapour pressure	Not applicable
Specific gravity	Not applicable
Solubility in water	Not soluble

10 STABILITY AND REACTIVITY

Conditions to avoid	Excessive heat, open flames
Stability	Stable under normal conditions
Material to avoid	Acids, bases and oxidising material
Hazardous decomposition	No data

11 TOXICOLOGICAL DATA

Not available

12 ECOLOGICAL INFORMATION

General	Prevent contamination of soil, ground and surface water.
---------	--



13 DISPOSAL CONSIDERATION

By incineration or sanitary landfill in accordance with local, state and federal regulations.

14 TRANSPORT INFORMATION

Road (U.S. -DOT)	not regulated
Air (IATA)	not regulated
Sea (IMDG)	not regulated

15 REGULATORY INFORMATION

European information	No published toxicological data available to assigne risk and safety phrases.
----------------------	---

OSHA, IARC, NTP Carcinogens lists	Non of the components is listed
-----------------------------------	---------------------------------

16 OTHER INFORMATION

Disclaimer of warranties and limitation of liability

The information in this MSDS is furnished without warranty, expresses or implied regarding its correctness. It was compiled from sources which we believe is reliable to the best of our knowledge. Russell IPM Ltd makes no warranty or representation to the suitability of the product for a particular purpose which may be used for and it can not be held liable for any damage or loss which may be consequence of the use of the product or the reliance of the information provided in the document incidentally or consequentially. it is the condition of supply that the suitability of the product for a particular application and the relevance of the information provide to the conditions of the application will be solely determined by the user.

