

# J.C. EHRLICH

*The 949 minimizes hydrogen sulfides and the build up of sludge thereby reducing odors, fecal matters, and grease compounds. The 949 dissolves gradually over 30 days (dependent upon flow rate) allowing for continuous waste treatment.*

## Directions for Use

- 1. Remove the 949 from carton.**
- 2. Drop into grease trap.**
- 3. Replace 949 every 30-45 days as needed with new product.**

## Precautions

Do not ingest or take internally. Avoid skin contact. Wear protective gloves and wash thoroughly after handling.

## Storage

Store in cool, dry place. Avoid contact with strong acids.

# J.C. EHRLICH

Lot#: 52293

Contents: 8 Blocks per Box

Visit us at: [jcehrlich.com](http://jcehrlich.com)

This product is formulated and manufactured under an ISO certified quality system in Beloit, WI.

# J.C. EHRLICH

*The 949 minimizes hydrogen sulfides and the build up of sludge thereby reducing odors, fecal matters, and grease compounds. The 949 dissolves gradually over 30 days (dependent upon flow rate) allowing for continuous waste treatment.*

## Directions for Use

- 1. Remove the 949 from carton.**
- 2. Drop into grease trap.**
- 3. Replace 949 every 30-45 days as needed with new product.**

## Precautions

Do not ingest or take internally. Avoid skin contact. Wear protective gloves and wash thoroughly after handling.

## Storage

Store in cool, dry place. Avoid contact with strong acids.

# J.C. EHRLICH

Lot#: 52293

Contents: 8 Blocks per Box

Visit us at: [jcehrlich.com](http://jcehrlich.com)

This product is formulated and manufactured under an ISO certified quality system in Beloit, WI.